

Digital Video Recorders TUTIS Series

TUTIS-4F3

4 Channel Network H.264 with Graphical User Interface



Features

- H.264 Video compression technology, support 4CH D1/CIF recording, support 4CH recording, network transmission & playback simultaneously
- Support dual- stream transmission for all channels
- Support multiplex operation: live, record, playback, backup, network transmission, mobile surveillance
- Support backup with USB Flash Disk, Movable hard disk, USB writer, Network
- Support 1 Channel BNC video output & 1 Channel VGA video output
- Support Multi- language OSD, PTZ control, E-mail alarm, digital Zoom & PIP preview
- Mobile phone surveillance (Win CE/ Symbian/ iPhone/ Blackberry/ Android)
- Support video channel hidden & S.E.Q for single channel, PTZ Preset & cruise control
- Video Management software & Network System Management
- Mouse, panel & remote controller operation

Specifications

Model No.	TUTIS-4F3
Operating system	Embedded Linux OS
Video Compression Format	Main Profile H.264
Video Input/ Video Output	4 Channels BNC/ 1Channel BNC, 1Channel VGA(1280*1024)
Audio Input/Output	4 channel RCA/ 1Channel RCA
Display Picture	1/4CH PIP/zoom
Digital Zoom ,PIP	Support
Multiplex Operation	Live/ display/ Playback/ Recording/ Backup Mobile phone Surveillance/ Network simultaneously
Display Resolution	PAL:D1(704*576) NTSC:D1 (704*480)
Recording Mode	Manual, Timer, Motion Detection, Alarm
Recording Frame Rate	D1@100fps,HD1@100fps, CIF@100fps
Recording Resolution	PAL:D1(704*576), HD1(704*288),CIF(352*288) NTSC:D1(704*480), HD1(704*240),CIF(352*240)
Recording Playback	1/4 Channel playback
Recording Backup	USB , Movable Hard Disk, USB Writer, Network
Network transmission	4 Channel real-time network transmission with QCIF resolution
Action with alarm	support
Email alarm	Send images to the designated email
Spot Alarm pop-up	support
PTZ Control	Pelco-D, Pelco-P, EverFocus
HDD	Support 1 SATA HDD, capacity to 2TB
Network and Protocol	RJ-45 10/100M via Ethernet, Support TCP/IP, PPPoE, DHCP, DDNS, UPNP, NTP
Browser	IE6.0-9.0/Firefox/Chrome/Opera/Apple Safari
Operating System	Windows XP/Vista/Win7 /Mac OS
Multi-Language	Support
Mobile Phone Surveillance	Windows/Symbian/iPhone/ Blackberry Operation System
Mouse Interface/ Backup Interface	USB 2.0
Remote Controller	Support
Power	DC 12V/ 3A
Working Temperature	0°C~ 50°C
Working Humidity	10%-90%
Certifications	CE, FCC and RoHS
Dimension	274(L)x214.5(W)x45(H)mm

Ordering Information

TUTIS-4F3 : 4CH, Embedded Linux OS, H.264, D1@ 100fps, HD1@ 100fps, CIF@ 100fps
Real time, Free Software included, 12VDC/3A Power supply included

* All product specifications are subject to change without notice

Modèls vary in different countries. Please visit EverFocus regional website for detailed ordering information.